

(8) 10/100BASE-TX ports

- ▶ 10/100 Unmanaged Switch
- ▶ Compact Size
- ▶ Internal power supply
- ▶ Store-and-Forward
- ▶ Auto-MDI/MDIX

MIL-S800i-v2



The industry's smallest 8-port compact switch with an internal power supply, the MIL-S800i-v2 auto-negotiates 10/100Mbps connections for fast and simple switching in workgroup, small office, and home environments. Features include:

Full/Half Duplex

Each port is capable of operating at full or half duplex, allowing up to 200 Mbps for end users. Flow control and back pressure minimize packet loss and maximize performance.

High-performance Switching

Non-blocking architecture assures rapid packet delivery, while 1K MAC address table and memory buffering provide swift lookup and packet forwarding.

MDI/MDIX

Provides automatic cable detection on 10/100BASE-TX ports for adjusting to straight-through or crossover cables during installation.

Ruggedized Chassis

Sturdy metal enclosures with wall holes mounts for installation in non-traditional environments

Straightforward Diagnostics

Perpetual port status provided via LEDs on top of switch to simplify troubleshooting.

Secure and Safe

Class B, UL, cUL, and TUV Certifications; conforms to IEEE 802.3, 802.3u, and 802.3x standards.

Ordering Info

MIL-S800i-v2

8-port 10/100BASE-TX Micro Switch with internal power supply

Specifications

Standards	IEEE Std. 802.3 10BASE-T Ethernet; IEEE Std. 802.3u 100BASE-TX Ethernet; IEEE Std. 802.3x full-duplex flow control
Network Interface	10BASE-T: RJ-45 Categories 3, 4, 5 100-ohm UTP; 100BASE-TX: RJ-45 Category 5 100-ohm UTP
Buffer Memory	768KB
Backplane	1.6 Gbps
Dimensions	Width: 6.3" [160 mm] Depth: 4.0" [100 mm] Height: 1.28" [32.5 mm]
Operating Temperature	0 to 45°C (32°F to 113°F)
Operating Humidity	5% to 95% (non-condensing)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Weight	0.45 kg (1 lb.)
Internal Power Supply	AC Power: 100 – 240 VAC Line Frequency: 50/60Hz
Power Consumption	4.5 Watts maximum
Compliance	Safety: UL, cUL, TUV/GS, CE Emissions: FCC Class B, CISPR 22 Class B, CE Mark, VCCI Class B
Installation	Integrated keyholes for wall mounting; twin magnets and desktop rubber feet included
Technical Support & Warranty	Free technical support and advanced warranty support for 5 years. Includes free telephone support, 24-hour support via web and ftp.



Transition Networks, Inc.
10900 Red Circle Drive
Minnetonka, MN 55343 USA
tel 952.941.7600
or 800.526.9267
fax 952.941.2322
info@transition.com
http://www.transition.com

©2008 Transition Networks, Inc.
All trademarks are the property of
their respective owners.
Technical information is subject to
change without notice.