



Wall-mounted i25 captures 180° field of view – no blind spots.

Indoors. Compact. Allround Secure.

The hemispheric camera for indoors delivers a high-resolution 180° panorama image with no blind spots. Easily replacing four standard CCTV cameras, just one i25 captures an entire room, wall-to-wall. The newly-designed wall mount form factor blends in with any environment.

i25 – The Perfect Overview

The MOBOTIX i25 is an indoor-only wall-mountable Hemispheric camera providing an allround view with just one lens. Only one camera is needed to view an entire room. The i25 can be mounted onto any indoor surface blending seamlessly into the surroundings.



Lens tilted down 15 deg.

Blends In

The i25 can be mounted onto any surface on a wall. The small form factor blends in with any environment. Fast installation with optional in-wall mounting kit.



Captures An Entire Room

The wall-mountable i25 captures an entire room with stunning wall-to-wall view, without any blind spots. Virtual PTZ on the live and recorded images is performed by the camera.



Image Correction Built-in

All of the image correction in the MOBOTIX Hemispheric cameras is handled by the camera's on board imaging analysis software. No additional PC or software required.



Day Or Night Capture

Available in both Day (color) and Night (B&W) models, which caters to the most challenging lighting conditions and a wide range of applications.

Technical Data

| | | | |
|-----------------------------------|--|-------------------------------------|--|
| Models | Day lens – color, Night lens – B&W | Lens Options | L12 (180° x 160°), L23 (92° x 68°), others optional |
| Image Sensors | 1/2,5" CMOS (5MP) | Sensor Resolution | Color: 2592x1944 pixels Black & White: 2592x1944 pixels |
| Max. Frame Rate (MxPEG) | MEGA/HD: 30 fps, QXGA: 15 fps, 5MP: 10 fps | Compression | MxPEG, M-JPEG, JPEG, H.264 (SIP video only) |
| DVR Recording | Internal: microSD Card External: PC/NAS (to 4 TB) | Audio | VoIP, sound recording using integrated microphone |
| Operating Conditions | IP30, 0 to +40 °C/+32 to +104 °F | Internal Sensors | Temperature, microphone, illumina- tion, shock detector |
| Image Processing | MxActivitySensor, VMD, image correction, backlight, MxAnalytics | Software (free of charge) | MxManagementCenter, MxControlCenter, MxEasy, MOBOTIX App |



環通科技有限公司
Netcare Technology Limited

Tel: (852) 2402 2178
Fax: (852) 2402 2190

Email: info@netcare.com.hk
Website: www.netcare.com.hk