



*The ceiling-mounted c25 delivers two 180° panorama images of a room*

## Indoor Ceiling Camera. Easy To Install.

With a diameter of only 12 centimeters and a weight of approximately 200 grams, the c25 is the smallest and lightest hemispheric MOBOTIX video complete system for fast ceiling mounting in protected indoor areas. Features include a light-sensitive 5-megapixel day or night sensor and MxAnalytics. Features all functions like the traditional Q25 outdoor camera.



### Two Models Available

The c25 is available as a hemispheric camera (L12, 180° panorama) to capture an entire room and with an L23 lens (92°), for example, to monitor the area around a cash register. Longer lens holder to support other lenses than hemispheric.



## Original MOBOTIX Hemispheric Technology

Unlike the devices of other manufacturers, hemispheric distortion correction in a MOBOTIX system takes place in the camera and not later on the computer using separate video management software. This drastically reduces the image data that needs to be transferred and saved.



## Typical Application Areas For The c25

Indoor applications in retail, supermarkets, public buildings, trade fair and exhibition spaces, hotels and recreation facilities, in residential buildings and for the surveillance of industrial production processes.



## Simple Installation In Suspended Ceilings

The c25 can be easily installed using a standard drill bit (105 mm in diameter) in suspended ceilings. The c25, which is connected to an Ethernet cable, is simply slotted in from below using raised spring clips and automatically secured in place.

### Technical Data

<b>Models</b>	Day lens – color, Night lens – B&W	<b>Lens Options</b>	L12 (180° x 160°), L23 (92° x 68°), others optional
<b>Image Sensors</b>	1/2,5" CMOS (5MP)	<b>Sensor Resolution</b>	Color: 2592x1944 pixels Black & White: 2592x1944 pixels
<b>Max. Frame Rate</b> (MxPEG)	MEGA/HD: 30 fps, QXGA: 15 fps, 5MP: 10 fps	<b>Compression</b>	MxPEG, M-JPEG, JPEG, H.264 (SIP video only)
<b>DVR Recording</b>	Internal: microSD Card External: PC/NAS (to 4 TB)	<b>Audio</b>	VoIP, sound recording using integrated microphone
<b>Operating Conditions</b>	IP20, 0 to +40 °C/+32 to +104 °F	<b>Internal Sensors</b>	Temperature, microphone, illumination, shock detector
<b>Image Processing</b>	MxActivitySensor, VMD, image correction, backlight, MxAnalytics	<b>Software (free of charge)</b>	MxManagementCenter, MxControlCenter, MxEasy, MOBOTIX App

## New MOBOTIX Indoor Camera Line

MOBOTIX offers the i25 and c25, two highly compact, discreet IP cameras for use indoors that deliver a wide range of features (for example, MxAnalytics video analysis tools). Matching accessories such as radar and surge protection modules are already in the works.



環通科技有限公司  
Netcare Technology Limited

Tel: (852) 2402 2178  
Fax: (852) 2402 2190

Email: info@netcare.com.hk  
Website: www.netcare.com.hk